

Peplink Balance multi-WAN router

Load Balancing. Unbreakable VPN. Bandwidth Bonding.



Peplink Balance Multi-WAN Router

The Peplink Balance multi-WAN router delivers Unbreakable VPN, SpeedFusion™ bandwidth bonding, and a host of other innovative technologies that let you take control of your WAN and improve Internet connectivity, all with one easy-to-manage device.

Connect Up to 13 Links from Multiple Providers

Connect any combination of DSL, cable, 4G LTE, and 3G links – up to 13 of them, from any ISP for anytime, anywhere connectivity. Whatever mix of connections you choose, the Balance intelligently distributes network traffic over all links connected anywhere on the network. You can also customize traffic flow and service availability with outbound policies and inbound load balancing settings, so you're always in control. And with the Balance's instant, automatic failover between links, you're always online, too.

Reduce MPLS Costs up to 90%

With the Balance and SpeedFusion, you can bond multiple links connected anywhere on your network for VPNs that can add speed and reliability to expensive MPLS deployments or replace them entirely. Because you can combine a variety of affordable DSL, MPLS, cellular, and other WAN links into one secure, high-bandwidth tunnel, you get unprecedented reliability and performance while saving big on connectivity costs.

SpeedFusion-powered Unbreakable VPN

The Balance can bond affordable DSL, cable, cellular, and other WAN links into a single secure and fast VPN tunnel using SpeedFusion technology. Packet-level failover across WANs within VPN tunnels is instant and seamless, so your voice calls and RDP sessions won't be interrupted when the Balance automatically switches between connections.

Monitor AP Usage Report and Create Guest Hotspot Easily from Your Balance

Our AP Controller makes it easy to manage your wireless network from a convenient, intuitive user interface built right into your Balance. You can easily manage your AP with graphical usage reports, and detailed event logs. Setting up a guest hotspot? The Balance's included captive portal and splash screen help you provide a secure, fast, and customized Internet experience for everyone.

Try out the Balance Web Admin Demo Now! peplink.com/demo

Break Internet Bandwidth Limits. Higher Speed. Extreme Reliability.

Internet Load Balancing

Boost network data rates, reliability, and flexibility while slashing connectivity costs with Peplink Internet Load Balancing technology. The Peplink Balance can distribute the traffic of up to 13 Internet links and route data using seven intelligent algorithms. It all adds up to high speeds and rock-solid dependability at a savings of up to 90% compared to solutions built on leased lines and other expensive links.

With the Peplink Balance, all your cable, DSL, leased line, cellular, and other links will work together to handle even the most demanding traffic, without lags or downtime. When you need more speed, add more connections.

Prioritize and Balance Traffic by Type or Application

The Peplink Balance incorporates 7 advanced link load balancing algorithms and customizable rules that put you in complete control of network data priorities. Just set your traffic priorities, including VoIP and custom application traffic, with a few clicks and let

Link Load Balancing

Current ISP

New DSL

New Cable

Local Network Peplink Balance Internet

Peplink take care of the load balancing and optimization details – day in, day out.

Count on 100% Uptime with Automatic Failover

Automatic Failover keeps your network up and running by continually checking the health of all connected links and routing traffic around inactive or intermittent connections. You can even customize Automatic Failover's behavior, specifying conditional or dedicated backup links that dynamically respond to network status.




Balance 1350

Replace MPLS with a Bonded VPN. SpeedFusion Shifts VPN Traffic into High Gear.

VPN for Branch Networking

Shift WAN data transfer, video delivery, VPNs, and more into overdrive with Peplink SpeedFusion. Peplink's patent-pending SpeedFusion true bandwidth bonding technology combines the bandwidth of up to 13 cable, DSL, 4G LTE/3G, and other links to drive high-speed, high-reliability, and high-security networking – all at a lower cost, with fewer maintenance headaches. Whether you're transferring a single file or sharing dozens of documents, video feeds, and VoIP conversations, SpeedFusion teams up all your links to make it happen faster and more dependably.



Maximum Performance. Minimum Hassle.

SpeedFusion increases performance across the board with intelligent bonding algorithms, advanced QoS, and video stream

optimization. With SpeedFusion, your network stays up and running smoothly, without micromanagement, even when network traffic's at its heaviest.

Ditch Expensive MPLS.

Looking for an alternative to expensive leased lines? SpeedFusion bonds the bandwidth of up to 13 cable/DSL, 4G LTE/3G, WiMAX, and other Internet connections from multiple providers, boosting transfer speeds and reliability while saving you money compared to single-line MPLS.



Mobile Bandwidth Bonding. Turbocharge Mobile VPNs.

4G LTE/3G Bandwidth Bonding

SpeedFusion, the technology at the heart of every Balance Multi-WAN and MAX Mobile router, bonds the bandwidth from multiple cellular connections. You get faster and more reliable mobile VPNs in every application. Plus, all your data is secured by military-grade encryption, and data volume is monitored and controlled to keep you under your usage cap and within budget.



Get the Speed You Need on the Road.

SpeedFusion Bandwidth Bonding automatically aggregates all connected 4G LTE/3G/WiMAX links to give you fast data transfers, smooth HD video, and blazing performance wherever you go. Need more speed? Just add cellular connections and let SpeedFusion take care of the details.

Enjoy Wired Reliability without the Wires.

SpeedFusion bonds cellular connections from multiple providers, continuously monitoring link connectivity and automatically switching to healthy connections in the event of link failure. Your network stays up and running, and you stay open for business.

Do More on the Road with SpeedFusion.

The speed, reliability, and security delivered by SpeedFusion open up a wide range of new mobile VPN applications in demanding, mission-critical fields, such as newscasting and public safety. In addition, transferring large files, such as those generated by digital production, photography, and POS activities, becomes practical and profitable wherever your mobile workforce roams.





All-in-One AP Controller Solution. Manage hundreds of APs. Built-in Captive Portal.

AP Controller Solution

Peplink's AP Controller solution combines an enterprise-grade wireless access point and centralized access point management in one easy-to-use and affordable package. Now you can manage wireless LAN networks of up to 1,500 Pepwave AP One devices using a single Peplink Balance. With Peplink's AP Controller solution, all your mobile devices, including iPhones, iPads, and Android devices, get the same reliable Internet connection that you've come to expect from Peplink – without the wires!

Built-in AP Controller

Simplify your network management by controlling your AP One access points using a centralized admin interface built into the Peplink Balance. Just connect an AP One to the network and it will be discovered by the Balance automatically, allowing you manage and set-up your access point instantly!



Easy Wi-Fi Portal

Peplink's AP Controller solution features a built-in captive portal, which allows you to provide Wi-Fi hotspot service to your customers or Wi-Fi access to your guests in a corporate environment. From showing a splash screen for free users to accept service terms to creating a user login for your paid customers, you can easily customize your Wi-Fi portal in just a few clicks.

Unified Network Management

With our AP Controller solution, you can manage all network connections, local client access, and user bandwidth policy using one single package. Administrators can monitor and generate reports on AP activity and bandwidth consumption, giving you complete and easy control over your network.



Specifications	<u>j îmm ñ</u>	pikk				6 6 66	peplink Bolance380	Popink Bassoce	1860 HEE	8
-	20/30/50	30 LTE	One	210/310	305	380	580	710	1350	2500
Designed For	Power User & Hom		e Office	Small Business	Mid-Size Business		Large Enterprise			
Ethernet WAN Ports	2/3/5	2	2 (GbE)	2/3 (GbE)	3 (GbE)	3 (GbE)	5 (GbE)	7 (GbE)	13 (GbE)	12 (GbE)
USB WAN Modem Port ¹	1	1	1	1	1	1	1	1	1	1 ⁸
Embedded LTE Modem	0	1	0	0	0	0	0	0	0	0
Recommended Users ²	1-25	1-25	1-50	1-50	50-500	50-500	300-1000	500-2000	1000-5000	5000-20000+
Router Throughput	100M	100M	1Gbps	100M	200M	200M	400M	800M	1.5G	8G
Load Balancing/Failover	•	•	•	•	•	•	•	•	•	•
Drop-In Mode	0	0	0	•	•	•	•	•	•	•
Inbound Load Balancing	0	0	0	•	•	•	•	•	•	•
SpeedFusion Bandwidth Bonding	0	0	O #	•	•	•	•	•	•	•
Number of SpeedFusion Peers ³	0	0	2	2	2/20 [%]	20	50	300	800	4000
SpeedFusion Throughput	0	0	30M	30M	60M	60M	80M	160M	350M	2G
PPTP VPN Server	•	•	•	•	•	•	•	•	•	•
IPsec VPN (Network-to-Network)	•	•	•	•	•	•	•	•	•	•
Manage Pepwave AP Series	•	•	•	•	•	•	•	•	•	•
Maximum Number of AP Supported	10	10	10	10	10/50*	10/50*	10/100*	20/250*	20/500*	20/1500 [*]
Manage Remote AP & Multiple Config Profiles	0	0	0	0	•°	•°	•°	• °	•°	•°
Bandwidth Usage Monitor	•	•	•	•	•	•	•	•	•	•
QoS for VoIP and E-commerce	•	•	•	•	•	•	•	•	•	•
User Groups Bandwidth Control	0	0	0	0	•	•	•	•	•	•
Web Blocking	•	•	•	•	•	•	•	•	•	•
LAN Ports	4 (GbE)	4 (GbE)	8 (GbE)	4 (GbE)	1 (GbE)	1 (GbE)	3 (GbE)	1 (GbE)	1 (GbE)	8 (GbE) / 2 (10 GbE)
1U Rackmount	0	0	0	•	•	•	•	•	•	•
High Availability	0	0	0	•	•	•	•	•	•	•
LAN Bypass	0	0	0	0	0	0	•	•	•	•
Dual Hot Swap Power Supply	0	0	0	0	0	0	0	0	0	•

For a list of supported modems, please refer to: http://www.peplink.com/modem ² Recommendation for sizing purposes only. No software restrictions applied. ³ Number of peer Peplink or Pepwave devices you can connect using SpeedFusion. [#] SpeedFusion is available as an optional feature. ** Balance 305 supports 2 PepVPN peers. With purchase of SpeedFusion License, the Balance 305 supports up to 20 SpeedFusion peers. Balance 710/1350/2500 comes with free license to manage 20 Pepwave AP devices respectively. To manage additional AP, an optional AP Controller license purchase is required. Balance 20/30/30 LTE/50/One/210/310 comes with AP Controller Standard, which supports one configuration profile with multiple SSIDs, meaning that all APs will share the same configuration, and you can only manage APs on the local physical LAN. Balance 305/380/580/710/1350/2500 comes with AP Controller Pro, which supports multiple configuration profiles with multiple SSIDs, and you can manage remote APs outside the local physical LAN. A Balance 2500 is available in two configurations with different LAN interfaces. ⁸ Requires a future firmware scheduled to be released in second half of 2014.

Ordering Information

Balance 30 LTE

Product Code	Carrier	Description
BPL-031-LTE-V-T	4G LTE (Band 13)	Embedded 4G model supporting 4G LTE (Band 13) network and providing automatic fall back to 3G CDMA (800/1900 MHz) as needed.
BPL-031-LTE-A-T	AT&T	Embedded 4G model supporting AT&T*/T-Mobile* 4G LTE network and providing automatic fallback to AT&T*/T-Mobile* 3G as needed. Technologies and frequency bands supported: 4G LTE (Band 4/17); WCDMA/HSDPA/HSUPA/HSPA+/DC-HSPA+ (800/850/1900/2100 MHz).
BPL-031-LTE-E-T *Requires a pre-activated SIM card.	4G LTE/HSPA+ (EU)	Embedded4Gmodelsupporting4GLTEforEUandworldwideGSMcarriersandprovidingautomaticfallbackto3Gasneeded. $Technologiesandfrequencybandssupported:4GLTE(Band1/3/7/8/20);WCDMA/HSDPA/HSUPA/HSPA+/DC-HSPA+(800/850/900/1900/2100MHz).$

Balance 2500

Product Code Description BPL-2500 12x GbE WAN ports and 8x GbE LAN ports. Supports LACP (802.3ad) NIC bonding.

BPL-2500-SFP 12x GbE WAN ports and 2x 10G SFP+ LAN ports.

Features WAN

Support for PPPoE, Static IP, DHCP WAN Link Health Check Bandwidth Allowance Monitor IPv6 Support USB 4G LTE/3G Modem Support Support for Dynamic DNS Services WAN Port Convertible into LAN Port

DHCP Server for LAN Clients Extended DHCP Options **DHCP** Reservation DNS Proxy for LAN Clients VLAN on LAN Support

Load Balancing

Intelligent Failover Session Persistence Per-Service Load Distribution Multiple Algorithms

Complete VPN Solution PepVPN/SpeedFusion

Site-to-Site VPN

Bandwidth Aggregation Intelligent Failover 256-bit AES Encryption Pre-shared Key Authentication Dynamic Routing X.509 Certificate Support PPTP VPN Server RADIUS, LDAP Authentication IPsec VPN (Network-to-Network) X.509 Certificate Support

Advanced QoS

User Groups Bandwidth Reservation Individual Bandwidth Limit Application Prioritization By User Groups SIP, HTTPS, VPN QoS Custom Application QoS

Networking

NAT and IP Forwarding Static Routes Port Forwarding Many to One, One to One NAT NAT Pool SIP ALG, H.323 ALG UPnP, NAT-PMP WINS Server OSPFv2 and RIPv2

Built-in Authoritative DNS Support for A, CNAME, NS, MX, PTR, SOA, SRV, TXT Records

AP Controller

Support for Pepwave AP Series Auto AP Discovery Auto AP Firmware Management AP Profile Configuration Wi-Fi usage statistics

Captive Portal

Support for Wired and Wireless LAN Clients Support RADIUS Authentication Support LDAP Authentication Time and Usage Quotas on Open Access Mode Built-in Customizable Splash Page

Security

DoS Prevention Stateful Firewall Web Blocking Support

Device Management

Web Administrative Interface Command Line Interface InControl Cloud Managment Router Utility Mobile App **Email Notification** Active Client & Session Lists **Bandwidth Usage Statistics** Syslog Service SNMP v1, v2c and v3

Specifications vary across different Balance models. For the most updated specifications, please refer to our website: http://www.peplink.com/balance/



www.peplink.com